


Designed by: QT Fabrics



Perfect Pillowcase

SIZE 20" x 37"





FABRIC REQUIREMENTS



Fabric A **30993 N** 3/4 YARD 1 BOLT



Fabric B 30994 E 1/3 YARD 1 BOLT



Fabric C 30997 0 1/8 YARD 1 BOLT

Information within gray box = Number of Bolts or Packs needed to make 12 Kits





We recommend that you carefully read through all instructions before getting started on your project.

CUTTING DIRECTIONS

Fabric A (pillowcase body), cut:

• (1) 27" x 41" (trim selvedge ends only)

Fabric B (top band), cut:

• (1) 12" x 41"

Fabric C (accent strip), cut:

• (1) 1½" to 3" x 41" (depending on how wide you want it to be)

CONSTRUCTION

- 1. Press Fabric C in half lengthwise, wrong sides together. Pin the folded Fabric C strip to the right side of the Fabric A along one 41" side, raw edges matching and sew through all layers ½" from edge. If your main fabric is directional, please consider which end is "up".) Sew the side seam with serger or French seam (see instructions for How to Make a French Seam below). Sew the bottom with the serger or French seam.
- 2. Sew the short side of Fabric B correct sides together with a $\frac{1}{2}$ " seam, forming a circle.
- 3. Pin the correct side of Fabric B to the wrong side of the case and sew with a $\frac{1}{2}$ " seam.
- 4. Turn under raw edge $\frac{1}{2}$ " and press. Turn to right side of case and align folded edge over top of previous stitching. Top stitch in place.

HOW TO MAKE A FRENCH SEAM

1. To make a French seam place the fabric wrong sides together and sew a $\frac{1}{8}$ " seam. Turn and press on seam with right sides together, then sew a $\frac{3}{8}$ " seam. This will encase the raw edge and give a nice finish to the inside of the case.