



SIZE 20" x 37"



FABRIC REQUIREMENTS

	Fabric A 30404 M ¾ YARD 1 BOLT		Fabric B 30408 N ⅓ YARD 1 BOLT		Fabric C 30408 G ⅛ YARD 1 BOLT	
---	---	---	---	--	---	--

Information within gray box = Number of Bolts or Packs needed to make 12 Kits

We recommend that you carefully read through all instructions before getting started on your project.

CUTTING DIRECTIONS

Fabric A (pillowcase body), cut:

- (1) 27" x 41" (trim selvedge ends only)

Fabric B (top band), cut:

- (1) 12" x 41"

Fabric C (accent strip), cut:

- (1) 1½" to 3" x 41" (depending on how wide you want it to be)

CONSTRUCTION

1. Press Fabric C in half lengthwise, wrong sides together. Pin the folded Fabric C strip to the right side of the Fabric A along one 41" side, raw edges matching and sew through all layers ½" from edge. If your main fabric is directional, please consider which end is "up". Sew the side seam with serger or French seam (see instructions for How to Make a French Seam below). Sew the bottom with the serger or French seam.
2. Sew the short side of Fabric B correct sides together with a ½" seam, forming a circle.
3. Pin the correct side of Fabric B to the wrong side of the case and sew with a ½" seam.
4. Turn under raw edge ½" and press. Turn to right side of case and align folded edge over top of previous stitching. Top stitch in place.

HOW TO MAKE A FRENCH SEAM

1. To make a French seam place the fabric wrong sides together and sew a ⅛" seam. Turn and press on seam with right sides together, then sew a ⅜" seam. This will encase the raw edge and give a nice finish to the inside of the case.