



SIZE 26" DIAMETER













FABRIC REQUIREMENTS

Fabric A 30709 J 1/2 YARD



Fabric B 30705 K 1/2 YARD



Fabric C 30707 E 11/8 YARDS



Fabric D 30796 Y **% YARD***

Fabric E 30796 Y 3/4 YARD**

Backing Only Cording Only

OTHER SUPPLIES:

- 6 yards of 1/8" cotton cording (if preferred purchase pre-made cotton-covered cording)
- 1½" Covered Button Kit
- Sewing Machine with Zipper Foot
- Basic Sewing Tools and Supplies
- Pattern Paper or Paper Bags at least 28" Square
- 2 yards Low-Loft Fleece



FLOOR POUF FEATURING HEAVY METALS



We recommend that you carefully read through all instructions before starting your project.

CUTTING DIRECTIONS

WOF = width of fabric from selvage to selvage

Fabric A, cut:

• (2) Cone Pieces for top (see step 1 below for instructions to create the cone pattern)

Fabric B, cut:

• (2) Cone Pieces for top

Fabric C. cut:

- (2) Cone Pieces for top
- (3) 5" x WOF for Gusset
- (1) 3" x WOF for Handle Subcut (2) 3" x 10" strips

Fabric D, cut:

• (1) Round Pattern Piece (see Step 2 below)

Fabric E, cut:

Fabric for cording (see Cording Instructions on right)

Low-Loft Fleece, cut:


- (2) Round Pattern Pieces
- (3) 5" x WOF for Gusset

CREATING PATTERNS

1. Make 1 copy of pattern #1 and 2 copies of pattern #2. Tape pieces together, flipping one piece #2 as shown.



2. To make the circle pattern, fold one piece of paper in half and in half again. Tie a pencil to a piece of string. Tack the end of the string to the corner fold and draw 131/2" quarter circle around the outer edge of the paper.




3. Cut out the paper circle pattern; unfold to reveal a 27" circle. Use pattern to cut Fabric D circle and Fleece circles.


CORDING INSTRUCTIONS


Use a 1/2" seam allowance for all sewing unless otherwise noted. RST = right sides together

- 1. Fold the *Fabric E* yardage diagonally from point to point to make a triangle, fold again to make a smaller triangle. Pin layers together to secure for steps 2 and 3.
- 2. Starting at the side and bottom fold, mark the whole piece into (8) 3" strips.



- 3. Cut out strips along the marked lines, being careful to keep layers together when cutting.
- 4. With RST join strips on the short ends with diagonal seams to form one long piece. Trim off corners.





5. Using a zipper foot, stitch the binding around the cord.






FLOOR POUF FEATURING HEAVY METALS




INSTRUCTIONS


1. With RST and using a 1/4" seam allowance, sew 1 Fabric A cone piece to 1 Fabric B cone piece; press seam open. Add a Fabric C cone piece to the B side of the AB unit to complete half of the pillow top; press seam open. Repeat to complete the second half.



2. With RST and a ¼" seam allowance, stitch the 2 half-pillow pieces together. Press seams open.




3. With RST, join the 3 gusset pieces to make a long gusset strip; press seams open. Trim length to 821/2". Join the ends to make the gusset. Repeat with the fleece pieces and baste to the wrong side of the gusset piece.




- 4. With RST, stitch the 2 handle pieces together along both long edges. Turn right side out, press and stitch close to both pressed edges.
- 5. Stitch the handle to the right side of opposite raw edges of the gusset to make the loop. Note: This handle is larger than the width of the gusset.

6. Using a zipper foot, stitch the cording to the right side of both raw edges of the gusset.



- 7. Baste the fleece circles to the wrong side of the pillow top and bottom.
- 8. With RST, pin the pillow top to one side of the gusset. Stitch in place.



- 9. With RST, pin the pillow bottom to the other side of the gusset. Stitch in place leaving a 6" opening for turning.
- 10. Turn right side out. Stuff the pillow and hand sew the opening closed.
- 11. Prepare the covered button referring to the manufacturer's instructions.
- **12.** Using a long needle, stitch the button to the center top of the pillow through the entire pillow to finish.

While all possible care has been taken to ensure the accuracy of this pattern, we are not responsible for printing errors or the way in which individual work varies.



