

SIZE 20" x 37"



### FABRIC REQUIREMENTS

	<b>Fabric A</b> <b>30794 X</b> ¾ YARD 1 BOLT		<b>Fabric B</b> <b>30795 X</b> ⅓ YARD 1 BOLT		<b>Fabric C</b> <b>29008 S0</b> ⅛ YARD 1 BOLT	
---	---	---	---	--	--	--

Information within gray box = Number of Bolts or Packs needed to make 12 Kits

*We recommend that you carefully read through all instructions before getting started on your project.*

## CUTTING DIRECTIONS

**Fabric A (pillowcase body)**, cut:

- (1) 27" x 41" (trim selvedge ends only)

**Fabric B (top band)**, cut:

- (1) 12" x 41"

**Fabric C (accent strip)**, cut:

- (1) 1½" to 3" x 41" (depending on how wide you want it to be)

## CONSTRUCTION

**1.** Press **Fabric C** in half lengthwise, wrong sides together. Pin the folded **Fabric C** strip to the right side of the **Fabric A** along one 41" side, raw edges matching and sew through all layers ½" from edge. If your main fabric is directional, please consider which end is "up.") Sew the side seam with serger or French seam (see instructions for *How to Make a French Seam* below). Sew the bottom with the serger or French seam.

**2.** Sew the short side of **Fabric B** correct sides together with a ½" seam, forming a circle.

**3.** Pin the correct side of **Fabric B** to the wrong side of the case and sew with a ½" seam.

**4.** Turn under raw edge ½" and press. Turn to right side of case and align folded edge over top of previous stitching. Top stitch in place.

## HOW TO MAKE A FRENCH SEAM

**1.** To make a French seam place the fabric wrong sides together and sew a ⅛" seam. Turn and press on seam with right sides together, then sew a ⅜" seam. This will encase the raw edge and give a nice finish to the inside of the case.